

## of

and

for

# A SYSTEM AND METHOD FOR EFFICIENTLY TUNING TO CHANNELS OF A VARIETY OF DIFFERENT BROADCAST TYPES

	1980	1981	1982	1983	1984	1985	1986	1987	1988	1989	1990	1991	1992	1993	1994	1995	1996	1997	1998	1999	2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	2027	2028	2029	2030	2031	2032	2033	2034	2035	2036	2037	2038	2039	2040	2041	2042	2043	2044	2045	2046	2047	2048	2049	2050	2051	2052	2053	2054	2055	2056	2057	2058	2059	2060	2061	2062	2063	2064	2065	2066	2067	2068	2069	2070	2071	2072	2073	2074	2075	2076	2077	2078	2079	2080	2081	2082	2083	2084	2085	2086	2087	2088	2089	2090	2091	2092	2093	2094	2095	2096	2097	2098	2099	2100	2101	2102	2103	2104	2105	2106	2107	2108	2109	2110	2111	2112	2113	2114	2115	2116	2117	2118	2119	2120	2121	2122	2123	2124	2125	2126	2127	2128	2129	2130	2131	2132	2133	2134	2135	2136	2137	2138	2139	2140	2141	2142	2143	2144	2145	2146	2147	2148	2149	2150	2151	2152	2153	2154	2155	2156	2157	2158	2159	2160	2161	2162	2163	2164	2165	2166	2167	2168	2169	2170	2171	2172	2173	2174	2175	2176	2177	2178	2179	2180	2181	2182	2183	2184	2185	2186	2187	2188	2189	2190	2191	2192	2193	2194	2195	2196	2197	2198	2199	2200	2201	2202	2203	2204	2205	2206	2207	2208	2209	2210	2211	2212	2213	2214	2215	2216	2217	2218	2219	2220	2221	2222	2223	2224	2225	2226	2227	2228	2229	2230	2231	2232	2233	2234	2235	2236	2237	2238	2239	2240	2241	2242	2243	2244	2245	2246	2247	2248	2249	2250	2251	2252	2253	2254	2255	2256	2257	2258	2259	2260	2261	2262	2263	2264	2265	2266	2267	2268	2269	2270	2271	2272	2273	2274	2275	2276	2277	2278	2279	2280	2281	2282	2283	2284	2285	2286	2287	2288	2289	2290	2291	2292	2293	2294	2295	2296	2297	2298	2299	2300	2301	2302	2303	2304	2305	2306	2307	2308	2309	2310	2311	2312	2313	2314	2315	2316	2317	2318	2319	2320	2321	2322	2323	2324	2325	2326	2327	2328	2329	2330	2331	2332	2333	2334	2335	2336	2337	2338	2339	2340	2341	2342	2343	2344	2345	2346	2347	2348	2349	2350	2351	2352	2353	2354	2355	2356	2357	2358	2359	2360	2361	2362	2363	2364	2365	2366	2367	2368	2369	2370	2371	2372	2373	2374	2375	2376	2377	2378	2379	2380	2381	2382	2383	2384	2385	2386	2387	2388	2389	2390	2391	2392	2393	2394	2395	2396	2397	2398	2399	2400	2401	2402	2403	2404	2405	2406	2407	2408	2409	2410	2411	2412	2413	2414	2415	2416	2417	2418	2419	2420	2421	2422	2423	2424	2425	2426	2427	2428	2429	2430	2431	2432	2
--	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	---

**WORKMAN, NYDEGGER & SEELEY**  
A PROFESSIONAL CORPORATION  
ATTORNEYS AT LAW  
1000 EAGLE GATE TOWER  
60 EAST SOUTH TEMPLE  
SALT LAKE CITY, UTAH 84111

## **BACKGROUND OF THE INVENTION**

### **1. Cross-Reference to Related Applications**

The present application is a non-provisional United States patent application based on a United States provisional patent application having a serial number 60/129,775, filed April 15, 1999, and entitled "Master Service Graph", which provisional application is incorporated herein by reference.

### **2. The Field of the Invention**

The present invention relates to electrical computers and data processing systems. Specifically, the present invention relates to a system and method for efficiently tuning to channels of a variety of different broadcast types.

### **3. The Prior State of the Art**

Multimedia data (e.g., audio, video, and other data) is broadcast using a variety of different transmission technologies.

One of the first major broadcast technologies is radio in which audio data is transmitted over terrestrial airwaves using an analog audio signal blended with a carrier wave. The analog audio signal is blended with the carrier wave in preparation for transmission by varying the amplitude of the carrier wave as in Amplitude Modulation (AM), or by varying the frequency of the carrier wave as in Frequency Modulation (FM). The blended carrier wave is then transmitted using an antenna over "terrestrial airwaves" meaning that the transmission occurs over the air without using a conductive medium and without the aid of an earth orbiting satellite. A radio receiver (also commonly referred to as simply a "radio") includes an antenna for receiving the blended carrier wave, a tuner for

1 extracting the analog audio signal from the carrier wave, and a speaker for converting the  
2 analog audio signal into sound.

3 A radio station may be licensed to transmit using a carrier wave of a specified  
4 frequency. For example, in the United States, AM radio stations may be licensed to  
5 broadcast at a specific frequency within the range of from 530 kilohertz to 1.7 megahertz.  
6 FM radio stations may broadcast at a specific frequency within the range of from 88  
7 megahertz to 108 megahertz.

8 Early television technology uses similar technology as radio technology. However,  
9 video data and audio data are both transmitted over terrestrial airwaves in the form of an  
10 analog signal blended with a carrier wave. In the United States, Very High Frequency  
11 (VHF) television channels 2 to 6 are typically transmitted using a carrier wave of a specific  
12 frequency in the range of from 55 to 88 megahertz. VHF channels 7-13 use a specific  
13 frequency in the range of from 174 to 216 megahertz. Ultra High Frequency (UHF)  
14 channels 14-83 use a specific frequency in the range of from 470 to 890 megahertz. The  
15 television receiver (also commonly called a "television") receives the television signal using  
16 an antenna, extract the video and audio data from the carrier wave using a tuner, converts  
17 the video data into video images using a display, and converts the audio data into sound  
18 using a speaker.

19 In radio and early television technology, broadcasting occurs by transmitting signals  
20 over terrestrial airwaves as described above. However, more recently, various other  
21 broadcast mediums are used such as cable and satellite networks. In cable networks,  
22 television and Internet data are transmitted over the cable network and to a television set or  
23 computer connected to the cable network. In satellite networks, the television and Internet  
24 data are transmitted to the television or computer using an earth orbiting satellite.

1           Until recently, television broadcasts used analog signals only. Currently, however,  
2 digital television broadcasts are available via satellite using the Digital Video Broadcast  
3 Satellite (DVB-S) standard. It is anticipated that in the near future, digital television  
4 broadcasts will also be available using terrestrial airwaves and cable. The FCC has  
5 mandated many aspects of the Advanced Television Standards Committee (ATSC) standard  
6 for broadcasting digital television signals over terrestrial airwaves and cable.

7           As apparent from the above, there are numerous types of audio or video broadcast  
8 types that either now exist or will likely exist including AM radio, FM radio, analog  
9 terrestrial airwave, digital terrestrial airwave, analog cable, digital cable, analog satellite,  
10 digital satellite and so forth. Some devices may be capable of receiving several of these  
11 broadcast types. Typically, a special tuner is required for each broadcast type. Thus, in  
12 order to tune to a desired channel, the viewer chooses the broadcast type in order to select  
13 the tuner. Next, the viewer selects the channel within that broadcast type. Thus, in order to  
14 tune to the desired channel, the viewer must have some knowledge about what channels are  
15 contained within each broadcast type. Typically, however, a viewer may not have full  
16 knowledge about what channels are offered on a certain broadcast type. This might  
17 especially be the case in broadcast types that offer numerous channels.

18           Also, acquisition of a digital television signal is a multi-step operation that can be  
19 significantly slow. For instance, once a tune request is received, the tuner first monitors the  
20 digital video stream in order to extract tuning information such as the program number or  
21 program identifier from the video stream. Once this necessary information is extracted, the  
22 tuner can finally tune to the desired channel. The initial step of extracting the necessary  
23 tuning information can take significant time. Thus, many consumers find that channel  
24 changing across digital channels can be an annoyingly slow process.

1  
2  
3  
4  
5

Thus, what is desired is a system and method for more efficiently tuning to a desired channel in a device that receives multiple broadcast types. Furthermore, it would be desirable if such a system and method provided a faster tune to digital channels.

## SUMMARY OF THE INVENTION

A tuning system that is capable of receiving a number of different broadcast types is described. These broadcast types might be analog or digital and may be via satellite, cable, the Internet, terrestrial airwave, and so forth.

The tuning system stores "service records" in a memory accessible by the tuning system. Each service record contains the complete set of information required to tune to a particular channel. For example, for an analog channel, the tuning information in a service record might include an identification of the tuner along with an identification of the channels such as call letters, a channel number, or a frequency. For a digital channel, the complete set of tuning information could include an identification of the tuner and other information usually found within the broadcast data stream (e.g., an MPEG-2 stream) such as a program identifier (i.e., PID), and a data structure of the data stream. In MPEG-2 digital broadcast, this information might be found in the Program Map Table (PMT) or in the Program Association Table (PAT) portions of the broadcast. Storing this complete set of tuning information saves considerable time tune-to-tune in digital channel changing since it is no longer necessary to extract tuning information from a sequence of tables represented in the digital video stream.

These service records are categorized within "service spaces" in any desired manner. One possible categorization is according to tuner type. For example, all channels obtainable by a cable tuner may be included in one service space, all channels obtainable by a satellite tuner may be included in another, and so forth. Further, service spaces may be independent of tuner type and may be categorized by some other parameter such as content. For example, service spaces may be dedicated to sports, news, children's television, educational channels, and so forth, regardless of what tuner is used to obtain that channel.

1 The service space may physically include a copy of the service record. However, to  
2 conserve on memory, the service space contains pointers to each service record that is part  
3 of that service space.

4 A viewer selects the service space in which the viewer desires to channel surf. The  
5 viewer might then be presented with a graphical user interface which lists all channels  
6 corresponding to the service records within that service space. Alternatively, no graphical  
7 user interface is provided. Instead, the viewer uses a remote control or other input device to  
8 channel up or down through the available channels that are provided by the service space.  
9 Thus, if a viewer desires to view only designated "favorite" channels, the viewer selects a  
10 "favorites" service space and selects the desired one of the favorite channels. In response to  
11 this selection, the tuning system uses the information within the selected service record to  
12 identify the correct tuner, and to cause that tuner to perform a tune of the selected channel.

13 This tuning system allows a viewer to quickly and efficiently channel surf through a  
14 category of channels even if those channels correspond to a variety of different broadcast  
15 types or tuners. Switching between broadcast types is automatic and does not require any  
16 additional user input such as a broadcast or tuner identification. Thus, the user need not  
17 memorize the channels associated with a particular broadcast or tuner. Instead, the channels  
18 are neatly organized as desired by the user.

19 Furthermore, tuning information related to digital channels is also stored in the  
20 service space. In a typical digital tuning system, the tuner obtains tuning information from  
21 the digital data stream such as an MPEG-2 broadcast. Often, it takes significant time for the  
22 tuner to extract the necessary tuning information from the digital broadcast data stream.  
23 This results in noticeable and often annoying time delays in channel surfing. Once accurate  
24 and reliable tuning information for a given channel is extracted from the digital video

0057E0" B2B2E60

1 stream, the tuning system described herein avoids time delay in digital tuning by quickly  
2 retrieving this previously extracted information from a cache memory rather than slowly re-  
3 extracting the information from the digital video stream. This information is validated and,  
4 if necessary, updated after the tune is complete. Thus, viewers of digital programming may  
5 obtain quick digital channel changes.

6 Additional objects and advantages of the invention will be set forth in the description  
7 which follows, and in part will be obvious from the description, or may be learned by the  
8 practice of the invention. The objects and advantages of the invention may be realized and  
9 obtained by means of the instruments and combinations particularly pointed out in the  
10 appended claims. These and other objects and features of the present invention will become  
11 more fully apparent from the following description and appended claims, or may be learned  
12 by the practice of the invention as set forth hereinafter.  
13



## BRIEF DESCRIPTION OF THE DRAWINGS

In order that the manner in which the above-recited and other advantages and objects of the invention are obtained, a more particular description of the invention briefly described above will be rendered by reference to specific embodiments thereof which are illustrated in the appended drawings. Understanding that these drawings depict only typical embodiments of the invention and are not therefore to be considered limiting of its scope, the invention will be described and explained with additional specificity and detail through the use of the accompanying drawings in which:

Figure 1 schematically illustrates a suitable operating environment for the present invention;

Figure 2 schematically illustrates the internal hardware features of the tuning system of Figure 1;

Figure 3 illustrates a controller attached to service records through service spaces in accordance with the present invention;

Figure 4 illustrates the display device of Figure 1 displaying a graphical user interface in which a viewer may select one of the service spaces of Figure 3 in which to channel surf;

Figure 5 illustrates the display device of Figure 1 displaying a graphical user interface in which a viewer may select one of the channels within the service space selected in Figure 4;

Figure 6 illustrates a flowchart of a method for accumulating the service records of Figure 3;

Figure 7 illustrates a flowchart for rapidly tuning to a digital channel;

Figure 8 illustrates a data structure having multiple time-dependent service records;

1           Figure 9 schematically illustrates a structure used to accumulate service records  
2 according to the method of Figure 6; and

3           Figure 10 schematically illustrates a data structure for implementing "Near Video On  
4 Demand" or NVOD using the principles of the present invention.  
5

## DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

In accordance with the present invention, a tuning system that is capable of receiving a number of different broadcast types is provided. These broadcast types might be analog or digital and may be via satellite, cable, Internet, terrestrial airwave broadcast, and so forth. The tuning system stores service records containing information required for tuning to a particular channel. These service records are categorized within service spaces in any desired manner. One possible categorization is according to tuner type. For example, all channels obtainable by a cable tuner may be included in one service space, all channels obtainable by a satellite tuner may be included in another, and so forth. Further, service spaces may be independent of tuner type and may be categorized by some other parameter such as content. For example, service spaces may be dedicated to sports, news, children's television, educational channels, and so forth, regardless of what tuner is used to obtain that channel. A viewer can select that service space and channel surf through the service space without having to specify the tuner or broadcast type used to obtain that channel.

The invention is described below by using diagrams to illustrate either the structure or processing of embodiments used to implement the system and method of the present invention. Using the diagrams in this manner to present the invention should not be construed as limiting of its scope. The embodiments of the present invention may comprise a special purpose or general purpose computer including various computer hardware, as discussed in greater detail below. The embodiments may further comprise multiple computers linked in a network environment.

Embodiments within the scope of the present invention also include computer readable media having stored thereon program code means such as executable instructions or data fields. Such computer readable media can be any available media which can be

1 accessed by a general purpose or special purpose computer. By way of example, and not  
2 limitation, such computer readable media can comprise RAM, ROM, EEPROM, CD-ROM  
3 or other optical disk storage, magnetic disk storage or other magnetic storage devices, or any  
4 other medium which can be used to store the desired executable instructions or data fields  
5 and which can be accessed by a general purpose or special purpose computer. Such  
6 computer readable media may also comprise a smart card. Combinations of the above  
7 should also be included within the scope of computer readable media. Executable  
8 instructions comprise, for example, instructions and data which cause a general purpose  
9 computer, special purpose computer, or special purpose processing device to perform a  
10 certain function or group of functions.

11 Although not required, the invention will be described in the general context of  
12 computer-executable instructions, such as program modules, being executed by a personal  
13 computer. Generally, program modules include routines, programs, objects, components,  
14 data structures, etc. that perform particular tasks or implement particular abstract data types.  
15 The invention will also be described by making reference to documents or records, which  
16 generally include or are defined by encoded data structures stored in a computer-readable  
17 medium or a computer memory device. The encoded data structures of records often  
18 represent words, numbers, or other expression and generally may be generated, edited,  
19 displayed and/or stored using a computer.

20 In one embodiment, the invention is used in a system known as WebTV®,  
21 manufactured by WebTV Networks, Inc., of Palo Alto, California, which uses a  
22 conventional television screen or another display unit in combination with a networked  
23 computer for composing, sending and receiving e-mail, browsing the World Wide Web  
24 (Web), accessing other segments of the Internet, and otherwise displaying information. A

1 WebTV<sup>®</sup> system uses standard telephone lines, Integrated Services Digital Network (ISDN)  
2 lines, cable lines associated with cable television service, or the like to connect to the  
3 Internet or other wide area networks.

4 Figure 1 schematically illustrates an environment 100 that represents a suitable  
5 operating environment for the present invention. The environment 100 includes a tuning  
6 system 102 that is capable of tuning to channels of a plurality of broadcast types whether the  
7 channel includes an audio signal, a video signal, another data signal, or any combination of  
8 these signals. The tuning system 102 may be a personal computer, a set top box for a  
9 television, an integrated unit within a television, or any other device that receives signals of  
10 more than one broadcast type. In one embodiment, the tuning system 102 is a WebTV<sup>®</sup>  
11 client.

12 The tuning system 102 includes a means and step for receiving a plurality of  
13 different broadcast types. This means for receiving may include any device or combination  
14 of devices capable of receiving one or more broadcast types. The present invention is not  
15 limited to any particular device or combination of devices. By way of example only, the  
16 means for receiving is shown in Figure 1 as the combination of devices enclosed by the  
17 dashed box 120.

18 The combination of devices may include one or more antennas for receiving  
19 channeled signals over terrestrial airwaves. For example, a radio antenna 104 receives radio  
20 signals (e.g., AM radio, FM radio, CB radio, and so forth), an analog television antenna 106  
21 for receiving analog television signals (e.g., VHF television and UHF television), and a  
22 digital television antenna 108 received digital television signals (e.g., ATSC standard, NTSC  
23 standard, DVB standard, and so forth). It should be noted that the function of several  
24 antennas may often be combined into a single antenna as is known in the art.

1 The combination of devices may also include one or more cables for receiving  
2 channeled signals over a cable network. For example, an analog cable 110 receives analog  
3 signals and a digital cable 112 for receiving digital signals. It should be noted that some  
4 cables may be capable of communicating both analog and digital signals as is known in the  
5 art.

6 The combination of devices may also include one or more satellite dishes for  
7 receiving channeled signals from a satellite. For example, an analog satellite dish 114  
8 receives analog signals and a digital satellite dish 116 receives digital signals. Furthermore,  
9 a single satellite dish may be able to receive both analog and digital satellite signals.

10 The combination of devices may also include an Internet connection 118 such as  
11 Plain Old Telephone Service (POTS), cable, satellite, Integrated Services Digital Network  
12 (ISDN), T-1, T-2, T-3, or any other type of Internet connection.

13 The combination of devices may also include receiver devices for receiving signals  
14 over any other medium as well. The combination of devices is coupled to the tuning system  
15 102 so as to route received signals to the tuning system 102.

16 The environment 100 of Figure 1 also includes a means for displaying viewable data  
17 (e.g., display device 122), a means for sounding audible data (e.g., speaker device 124), and  
18 a means for receiving instructions (e.g., input device 126).

19 The display device 122 may be any device capable of producing video images from a  
20 video signal. For example, the display device 122 may be a computer monitor, digital  
21 television display, a standard television display, a flat panel display, a projection device, or  
22 any other display device.

1 The speaker device 124 may be any device capable of producing sound from an  
2 audio signal. The speaker device 124 may be integrally positioned with respect to the  
3 display device 122, or may be moveable with respect to the display device 122.

4 The input device 126 is communicatively coupled to the tuning system 102 so that  
5 when a viewer uses the input device 126 to enter the instructions, the input device 126  
6 generates a signal that is received by the tuning system 102, the signal representing the user  
7 entered instruction. The input device 126 may be, for example, a remote wireless control  
8 (i.e., a remote control) or a hardwired control device, and may be integrated with the tuning  
9 system 102, or moveable with respect to the tuning system 102.

10 Figure 2 is a block diagram of the internal features of the tuning system 102 of  
11 Figure 1. The operation of the tuning system 102 is controlled by a Central Processing Unit  
12 (CPU) 202, which is coupled to an Application-Specific Integrated Circuit (ASIC) 204. The  
13 CPU 202 executes software designed to implement features of the tuning system 102  
14 including some of the features of the present invention. The ASIC 204 contains circuitry  
15 which is used to implement certain functions of the tuning system 102. The ASIC 204 may  
16 include more than one physical component such as a demodulator, any needed decoders  
17 such as an MPEG decoder or other video decoders as appropriate to the broadcast signals  
18 received. The ASIC 204 may also include a graphics processor for performing specialized  
19 graphics functions on received video as needed. The details of the ASIC 204 are not  
20 important to the implementation of the present invention as long as the tuning system 102 is  
21 able to tune to a selected channel using service records.

22 Instructions, data, and other software necessary for the herein described operation of  
23 the CPU 202 and ASIC 204 may be stored, for example, in a read-only memory (ROM) 206,  
24 a random-access memory (RAM) 208, and/or a mass storage device 210. Mass storage

device 210 may be any mass memory means capable of storing large amounts of data such as a magnetic or optical disk drive. The ROM 206, the RAM 208 and the mass storage device 210 are communicatively coupled to the ASIC 204 so as to be readable by the ASIC 204 and so that data may be written from the ASIC 204 to the RAM 208 and possibly to the mass storage device 210.

The tuning system 102 also includes a number of tuners which are designed to tune to particular broadcast types. Table 1 lists the tuners in the left column, the receiving device that the tuner is attached to in the middle column, and the function of the tuner in the right column.

Tuner Name	Attached Receiving Device	Tuning Function
Radio Tuner 212	Radio Antenna 104	Radio (e.g., AM, FM, CB)
Analog Television Tuner 214	Analog Television Antenna 106	Analog Television (e.g., VHF, UHF)
Digital Television Tuner 216	Digital Television Antenna 108	Digital Television (e.g., ATSC, NTSC, DVB)
Analog Cable Tuner 218	Analog Cable 110	Analog Tuning (e.g., television, radio)
Digital Cable Tuner 220	Digital Cable 112	Digital Tuning (e.g., television, radio)
Analog Satellite Tuner 222	Analog Satellite Dish 114	Analog Tuning (e.g., radio and television)
Digital Satellite Tuner 224	Digital Satellite Dish 116	Digital Tuning (e.g., radio and television)
Internet Tuner 226	Internet Connection 118	Internet Tuning (e.g., POTS, cable, satellite, ISDN, T-1, T-2, T-3)

Table 1

The tuning system 102 of Figures 1 and 2 can have access to a variety of different broadcast types including radio terrestrial airwave (i.e., traditional radio), analog television



1 terrestrial airwave (i.e., traditional television), analog cable (e.g., traditional cable  
2 television), digital cable, analog satellite, digital satellite, and Internet broadcasts. However,  
3 a suitable tuning system for use with the present invention may also tune to just a subset of  
4 these broadcast types.

5 In a typical tuning system that receives more than one broadcast type, the user must  
6 first specify the broadcast type by selecting a tuner before selecting a channel. This tuner  
7 selection can take some time. If the user is constantly switching between tuners, the tuner  
8 selections can be burdensome and annoying. Furthermore, the user may often not have full  
9 knowledge of what channels are available on a particular broadcast type. Thus, the user may  
10 select a particular tuner only to find that the user is not interested in any of the channels  
11 within that broadcast type. The present invention significantly reduces these difficulties by  
12 eliminating the need to select a tuner and by categorizing channels according to any manner  
13 desired by the user, not just by tuner or broadcast type.

14 Specifically, embodiments within the scope of the present invention include a means  
15 or step for storing a plurality of service records. In this description and in the claims, a  
16 “service record” is defined as a compilation of information needed to tune to a channel.  
17 This channel may be a television, radio, or data channel. In additional, a Web page is also  
18 included within the definition of a channel in which case “tuning to” the Web page would  
19 involve downloading the Web page over a network such as the Internet. A “tuner” for  
20 tuning to a Web page would be a network connector such as a modem, a network card, or  
21 any other device capable of receiving Web pages over a network.

22 While, the information in the service record includes tuning information, the service  
23 record may also optionally including other information such as the name and number of the  
24 corresponding channel. In the embodiment of Figures 1 and 2, the tuning system 102 stores

1 service records in ROM 206, RAM 208, or mass storage device 210. However, one skilled  
2 in the art will recognize that any memory having sufficient capacity can also store the  
3 service records.

4 Figure 3 illustrates several service records 301-310. For clarity, assume that the  
5 tuning system 102 has access to three different broadcast types and associated tuners  
6 including analog cable, DVB-S satellite television, and terrestrial airwave television. Each  
7 service record 301-310 includes an associated identifier 301a-310a that is used by the tuning  
8 system 102 to identify the service, and includes other tuning information 301b-310b,  
9 respectively. Some of the service records (namely, service records 301-304) are for tuning  
10 to channels of analog cable television. Service records 305-307 are for tuning to channels of  
11 digital satellite television. The remaining service records 308-310 are for tuning to  
12 traditional terrestrial airwave television.

13 Service records 301-304 and 308-310 are for tuning to analog channels. In order to  
14 tune to a channel of an analog broadcast types such as analog cable television or traditional  
15 terrestrial airwave television, all that is needed is an identification of the broadcast type (i.e.,  
16 a tuner identification) and an identification of the channel. This channel identification could  
17 be in the form of a channel number (Channel 2, 3, 4, 5, and so forth), in the form of a  
18 frequency, in the form of call letters, or any other form that identifies the channel.

19 Service records 305-307 are for tuning to digital channels. In order to tune to a  
20 channel of a digital broadcast type such as digital satellite television, the service records  
21 305-307 include an identification of the broadcast type or tuner. The service records 305-  
22 307 may also include a channel identification such as a channel number. This is the  
23 minimum information needed to tune to the digital channel. The tuner can extract any other  
24 tuning information from the digital broadcast itself.

1 Unfortunately, the extraction of this tuning information from the digital broadcast  
2 can take significant time. Specifically, in MPEG-2, the program number and program  
3 identifier (i.e., PID) are found in the Program Association Table (PAT) portion of the video  
4 stream. Furthermore, the bit stream type (e.g., audio, video, control, and so forth) and  
5 location are found in the Program Map Table (PMT) portion of the video stream. Thus,  
6 the tuner must monitor the video stream first to obtain the information before a tune can  
7 occur. If the user changes channels frequently, the user may be inconvenienced by the  
8 constant delay between channel changes. This is why channel changes in conventional  
9 digital television devices are rather sluggish, especially when channel changes occur  
10 frequently.

11 In accordance with the present invention, the tuning system 102 does not always  
12 need to monitor the digital broadcast to extract tuning information. Instead, the service  
13 records 305-307 may also include the tuning information that is normally extracted from the  
14 digital broadcast itself. In this case, the digital tuning occurs faster and channel surfing is  
15 less sluggish than in conventional digital tuning systems.

16 A service record for a Web page might include, for example, the Uniform Resource  
17 Identifier for the Web page or any other information needed to access the Web page. While  
18 the present invention may be used to access Web pages, the remainder of this description  
19 will focus primarily on a tuning system in which broadcast channels are tuned to and  
20 accessed.

21 Embodiments within the scope of the present invention also includes a means or step  
22 for categorizing these service records 301-310 into service spaces. In this description and in  
23 the claims, a "service space" is defined as a collection of service records. In the

1 embodiment of Figure 3, service spaces 311-315 are composed of pointers to all the service  
2 records included in the service space.

3 The service spaces may have any desired characterization. For example, the service  
4 spaces may be characterized according to tuner or broadcast type. For example, service  
5 space 311 includes all cable television service records 301-304, service space 313 includes  
6 all satellite television service records 305-307, and service space 315 includes all airwave  
7 television service records 308-310. The service spaces may also be characterized according  
8 to desirability such as in service space 312 which includes the viewers favorite service  
9 records 303, 305 and 308. There is also a "master" service space which includes all service  
10 records 301-310 as does the "master" service space 314. The service spaces may also be  
11 characterized according to content such as sports, cartoons, news, movies, children,  
12 educational, or by any other category desired by the viewer.

13 The dotted arrowed lines in Figure 3 represent that the service space originating the  
14 arrowed line includes a pointer for the service record indicated by the arrowed line. For  
15 example the "favorites" service space 312 includes pointers A, B, and C for pointing to  
16 service records 303, 305 and 308, respectively. The other service spaces 311-313 and 315  
17 contain similar pointers for pointing to their respective service records. For clarity, the  
18 individual pointers for the "master" service space 314 is not shown. However, arrow line  
19 316 represents all of the pointers of the "master" service space 314.

20 Note that each service records may be shared with several service spaces. For  
21 example, service record 303 is shared by the cable television service space 311, the  
22 "favorites" service space 312, and the "master" service space 314. Thus, memory is  
23 conserved since each service space only contains a pointer for the service record, rather than  
24 the entire service record.

As each service record is created (using the means for accumulating service records described below), the tuning system 102 may include that service record in the "master" service space. A graphical user interface may be displayed on the display device 122 in response to a viewer-entered input at the input device 126. Using this input device 126 and the graphical user interface, the viewer may create new service spaces, delete old service spaces, add a service record to a service space, delete a service record from a service space, and so forth. Thus, the viewer can customize service spaces as desired.

Service spaces may also temporarily point to a service record. For example, in the case of pay per view, a service space may include a pointer to a service record that describes a pay-per-view program. If the viewer selects this program, the service space is automatically altered to include a pointer to the pay-per-view program.

A user can select one of the service records (i.e., pointers) within one of the service spaces using a means or step for receiving a selection of one of the service records in one of the service spaces as is now described. A controller 330 controls which service spaces are active, and controls the channel changing process within that active service space.

Specifically, a graphical user interface as shown in Figure 4 may be displayed on the display device 122. Each of the titles of the service spaces 311-315 is displayed such as cable service space title 411, "favorites" service space title 412, satellite service space title 413, "master" service space title 414, and airwave television service space title 415, respectively. As an alternative to initially displaying the service space titles 411-415, the "master" service space 314, or another service space 311-313 or 315 may be selected as the default service space thereby eliminating the need to select a service space when channel surfing is desired within the default service space. In this case, the other service spaces may be selected by inputting a predetermined input signal from the input device 126. Returning

to the embodiment of Figure 4, a viewer may select a service space (e.g., “favorites” service space 312) by activating the selecting the appropriate service space title (e.g., the “favorites” service space title 412) using the input device 126. The selection of the “favorites” service space 312 is indicated by the position of the arrow 416 on the graphical user interface.

Figure 5 shows a graphical user interface displayed on the display device 122 in response to a selection of the “favorites” service space 312 of Figure 4. In response the selection, the pointers of all of the service records in the “favorites” service space 312 are used to obtain a description of the channel corresponding to the service records within the service space 312 including service records 303, 305 and 308. The resulting description is then displayed on the display device 122. In the example shown in Figure 5, the favorite service records 303, 305 and 308 correspond to a description 503 of the gardening channel, a description 505 of the weeding channel, and a description 508 of the trimming channel, respectively.

Specifically, the pointer A of the “favorites” service space is used to obtain a description 503 contained in the service record 303. Pointers B and C are used to obtain descriptions 505 and 508 of service records 305 and 308, respectively. The descriptions A, B, C, might include the channel number, call letters, frequency, or any other identifying information recording the channel corresponding to the service space. In the example of Figure 5, the descriptions 503, 505 and 508 represent a channel title.

The viewer may now use the input device 126 to select the desired channel. For example, assume the viewer indicates the “gardening channel” description 503. The controller 330 then determines that the viewer has selected the channel corresponding to the service record 303. The controller then tunes to the corresponding channel using a means or step for tuning to a channel corresponding to the selected service record using the tuning



Once the selection of the desired service records is received, the controller 330 tunes to the selected service records using a means or step for tuning to a channel corresponding to the selected service record using the tuning information provided in the service record. Specifically, the controller 330 uses the information within the selected service record to select the appropriate tuner and to tune to the corresponding channel.

For example, service records 301-304 include an indication that the channels are tunable through the cable tuner 331, service records 305-307 include an indication that the channels are tunable through the DVB-S tuner 332, and service records 308-310 include an indication that the channels are tunable through the terrestrial television tuner 333. Once the correct tuner is selected, the other tuning information within the selected service record is used to tune to the desired channel. This other tuning information will differ depending on the tuner type and has been described above with respect to the means or step for storing a plurality of service records and Figure 3.

Note that the "favorites" service space 312 contains service records of a variety of different broadcast types including analog cable, digital satellite and analog terrestrial airwave. Also, tuning to the channels within the "favorites" service space requires the use of several tuners such as cable tuner 331, DVB-S tuner 332, and terrestrial television tuner 333 (see Figure 3). Conventionally, to change channels between broadcast types, a viewer would have to select the broadcast type as well as the channel within the broadcast type. However, as described above with the present invention, the viewer may change channels within a service space but between broadcast types by issuing a simple channel change instruction. The viewer need not be concerned with the particular broadcast type which delivers the desired channel. Thus, the present invention simplifies the tuning experience for the viewer for tuning systems that receive multiple broadcast types.



1 Up to this point, this description has assumed the existence of the service records  
2 301-310. In order to obtain these service records 301-310, embodiments within the scope of  
3 the present invention include means or step for accumulating the plurality of service records  
4 301-310. An example of a method for accumulating the plurality of service records is  
5 shown in Figure 6.

6 The service records 301-310 may be initially accumulated by each tuner 331-333  
7 monitoring the digital data stream or analog broadcast (step 610) to determine which  
8 channels are available (step 620). A channel may be determined to be available (step 620)  
9 when the channel is tuned and a clear signal is received. Once a channel is determined to be  
10 available (step 620), the tuning system 102 determines whether a service record already  
11 exists for that channel (decision block 630). If a service record already exists (yes in  
12 decision block 630), the method returns to step 620 where the next available channel is  
13 determined. If a service record doesn't exist (no in decision block 630), a service record is  
14 created for that channel (step 640), and the parameters used by the tuner to tune to that  
15 channel are included in the service record (step 650). Then the method repeats for all  
16 available channels for a given tuner, and for all tuners within the tuning system 102.

17 The tuning system 102 may repeat this method at predetermined intervals to detect  
18 new available channels for each tuner. The method may be performed during low usage  
19 times so as not to interfere with the viewer's normal viewing of the display device 122. In  
20 addition, at the start of the predetermined interval when the tuning system 102 is to perform  
21 the service record check, the tuning system 102 may optionally check to see if the tuning  
22 system 102 is already in use. If not in use, the tuning system 102 will perform the method of  
23 Figure 6 or another equivalent service record accumulation method. In addition, service  
24 record accumulation may be terminated when the tuning system 102 detects that the viewer



1 In addition to providing a simple method for tuning to channels of a variety of  
2 different broadcast types, the tuning system 102 performs fast tunes to digital channels.  
3 Conventional digital television tuners take significant time tuning to a digital channel since  
4 digital tuning is typically a multi-step operation. Once a tune request is received, the tuner  
5 monitors the digital video stream to extract all necessary information needed to tune such as  
6 the program number or the program identifier. This information is not always immediately  
7 available in the video stream. Thus, the tuner must monitor the digital video stream for  
8 some time before extraction can begin. Once the information is extracted, the tuner uses this  
9 information to perform the actual tune operation.

10 In contrast, the tuning system 102 often performs a fast tune to the digital channel by  
11 sometimes eliminating the need to extract tuning information from the digital video stream.  
12 The fast tuning method is described with respect to the flowchart of Figure 7. First, the user  
13 selects a service record (step 710). Then, the controller 330 uses the information in the  
14 service record to perform the tune (step 720). Thus, instead of the time consuming process  
15 of extracting the tuning information from the digital video stream, the controller 330 reads  
16 the information from the corresponding service record. In this case, the tune would be  
17 successful (YES in decision block 730) and the method would end.

18 However, the information within the service record may be incorrect or outdated. In  
19 this case, the tune would be unsuccessful (NO in decision block 730). The controller 330  
20 would then update the record (step 740) and attempt to once again tune to the channel using  
21 the updated information (step 720).

22 Although each service record may be valid permanently, there will often be times  
23 when the desired service record will depend on the time. This is the case, for example,  
24 where an electronic program guide accessible by the tuning system 102 indicates that

1 beginning at 2:00 am on March 1, 2000, a given channel's broadcast source will change  
2 from broadcaster XYZ to broadcaster WXY. Also, this may occur when a channel is  
3 shared by different broadcasters with one broadcaster broadcasting during the day, and  
4 another at night. Figure 8 illustrates a structure 800 that enables this time-dependent tuning.

5 A service space may have service records that are organized according to channel.  
6 For example, service record 838 corresponds to a channel 38. If channel 38 is selected, the  
7 information within the service record 838 is used to perform the tune. A service record 839a  
8 correspond to channel 39. However, service record 839a includes time limitations and a  
9 pointer P to another service record 839b. If the current time does not meet the time  
10 conditions, then the pointer P is used to obtain the next service record 839b. If the time  
11 conditions of service record 839b are not satisfied, the pointer P' is used to access service  
12 record 839c and so forth until a service record 839d is found that does correspond to the  
13 current time. Then, that service record 839d is used to tune to the appropriate program.

14 The present invention may also be used to implement "Near Video-On-Demand"  
15 (NVOD). "Video-On-Demand" is a technology that allows a user to select a program such  
16 as a movie for viewing and then almost immediately begin viewing the program. Video-On-  
17 Demand thus requires that each possible program selection be configured to be immediately  
18 available once selected. "Near Video-On-Demand" is also a technology that also allows a  
19 user to select a program for viewing. However, the user may typically have to wait a little  
20 while before the selected program is available. While there is some inconvenience in having  
21 to wait for the program versus having the program immediately available, Near Video-On-  
22 Demand does have the restraint that each possible program selection be configured to be  
23 immediately available. Near Video-On-Demand thus allows more flexibility in accessing a

1 source for the selected program. In the example that follows, the source for the selected  
2 program is one or more broadcast signals.

3 The implementation of Near Video-On-Demand using the principles of the present  
4 invention will be illustrated with reference to Figure 10. The data structure 1000 is created  
5 in response to a request to access (e.g., view or record) a certain program called  
6 "PROGRAM XYZ" in the example of Figure 10. PROGRAM XYZ may represent a movie,  
7 a talk show, a situation comedy episode, or any other desired broadcast segment.

8 In response to a request for PROGRAM XYZ, a service space is created for  
9 PROGRAM XYZ such as PROGRAM XYZ service space 1002 if such a service space does  
10 not already exist. Next, a search is performed to find all channels that are going to show  
11 PROGRAM XYZ in a time period close to the current time if PROGRAM XYZ is to be  
12 viewed as soon as possible, or in a time period close to some future time if PROGRAM  
13 XYZ is to be viewed at some future time. In the example, the time of the request is assumed  
14 to be 1:10 pm for illustrative purposes and it is also assumed that PROGRAM XYZ is to be  
15 viewed as soon as possible. The search may evaluate any source of programming  
16 information that may divulge what programs are being shown on what channels and at what  
17 time. Such a source may include, for example, an Electronic Program Guide. In the  
18 example of Figure 10, four channels are found that will show PROGRAM XYZ at a time  
19 close to the current time. A service record is created for each channel showing PROGRAM  
20 XYZ.

21 The first service record 1004 indicates that PROGRAM XYZ begins at 1:00 pm on  
22 channel 180. The second service record 1006 indicates that PROGRAM XYZ will begin at  
23 1:15 pm on channel 200. The third service record 1008 indicates that PROGRAM XYZ will  
24 begin at 1:30 pm on channel 220. The fourth service record 1010 indicates that PROGRAM

1 XYZ will begin at 1:45 pm on channel 240. A pointer to each of these service records is  
2 included in the PROGRAM XYZ service space 1002 thus creating the data structure 1000.

3 The data structure 1000 is then used to select the appropriate service record to be  
4 used to tune. Since the current time is 1:10 pm, a logical choice of service records would be  
5 service record 1006 since it requires the least waiting time for PROGRAM XYZ without  
6 missing any of PROGRAM XYZ. The tuning information for the selected service record  
7 1006 is then used to tune to the appropriate channel which is, in this case, channel 200. The  
8 viewer would then wait for five minutes for PROGRAM XYZ to begin. The program would  
9 begin at 1:15 pm and then would typically be viewed until the end time of the program  
10 which is 2:15 pm being apparently a one-hour program.

11 The use of service records and service spaces according to the principles of the  
12 present invention allows a great deal of flexibility in optimizing the viewing experience. For  
13 example, suppose that in the example of Figure 10, that five minutes after the viewer begins  
14 viewing PROGRAM XYZ on channel 200, the viewer is distracted by other matters such as  
15 a 25 minute telephone call received at 1:20 pm. The user may then activate a pause function  
16 in the tuning system. At 1:45 pm, 25 minutes later, the viewer returns to the tuning system  
17 to continue viewing. When the viewer activates a resume function to continue viewing, the  
18 tuning system intelligently determines the appropriate channel to return to, even if that  
19 channel was not the one viewed at the time of the pause. In this case, the tuning system  
20 assumes, or the viewer has indicated, that none of PROGRAM XYZ is to be missed. The  
21 tuning system then determines what channel to tune to accomplish this objective. Service  
22 record 1010 indicates that PROGRAM XYZ begins at the time the resume function is  
23 activated at 1:45 pm. Thus, the tuning system uses service record 1010 to tune to channel  
24 240 to resume viewing the program.

1 If the viewer is not to see the first five minutes of PROGRAM XYZ again, the tuning  
2 system may determine the point in PROGRAM XYZ where the viewer activated the pause  
3 function. In this case, that point is five minutes after the beginning of PROGRAM XYZ.  
4 The tuning system would thus tune to channel 240 at 1:50 pm to resume PROGRAM XYZ  
5 at precisely the point where the viewer paused PROGRAM XYZ. The viewer need never  
6 know that the program was resumed on a different channel. From the viewer's perspective,  
7 PROGRAM XYZ was provided automatically with some wait time between the request to  
8 view and the beginning of the program, and with some wait time after the resume function  
9 was activated until the program was resumed.

10 The present invention may be embodied in other specific forms without departing  
11 from its spirit or essential characteristics. The described embodiments are to be considered  
12 in all respects only as illustrative and not restrictive. The scope of the invention is,  
13 therefore, indicated by the appended claims rather than by the foregoing description. All  
14 changes which come within the meaning and range of equivalency of the claims are to be  
15 embraced within their scope.

16 What is claimed and desired to be secured by United States Letters Patent is:  
17